



H140T

4x2

Hauler Tractor



B U I L T A F R I C A T O U G H

Designed and Manufactured in South Africa



Axles

Front : Desmond non drive (4x2)
Pivoting steering axle

Rear Type: Rockwell
Rear Model: PRC673P

Steering

- Fully hydraulic orbital controlled steering with double acting cylinder
- Full flow filtration
- Working pressure - 1500 Psi (10.3 Mpa)

Tyres

Front : 10.5 x 16" (14 Ply)
Rear : 520 85 R38

Electrics

Voltage : 24 Volt
Battery : 2 x 12 Volt sealed type
Alternator: 24 Volt / 70 Amp

Brakes

Type : S-Cam air brake
Size : 16.5" x 5" drum brake
Park Brake : Spring applied with emergency failsafe

Hitch

- Hydraulically operated ball type hitch with weight transfer and safety lock (standard 90mm ball)
- Plus conventional type draw bar pin hitch

Optional Equipment

- Cab heater
- Tachograph
- Radio/Tape
- Custom painting
- Stainless steel exhaust
- Air conditioner

Pneumatic System

Capacity : 20 Liters
Working Pressure : 120 Psi (8.1 Bar) Unloader valve controlled

Engine

Type : Cummins
Model : 6 BTA 5.9 Turbocharged
Capacity : 5.9 Litres
Power : 149kW @ 2500 RPM
Torque : 814Nm @ 1500 RPM

Transmission

Type : Allison
Model : 3000 World Series
Gearing : Full power shift/automatic with downshift protection
Gears : Forward - 6
Reverse - 1
Speed : 40Km/H
Torque Converter : Type 411 with lock-up clutch

Hydraulic System

Oil Capacity : 60 Liters
Pumps : Fixed displacement gear driven
Working Pressure : 2200 Psi (15.1 Mpa) Full flow filtration

Service Capacities

Cooling system : 32 Litres (50% Anti-freeze)
Engine Crankcase : 16 Litres
Rear Axle Differential: 45 Litres
Transmission : 18 Litres
Diesel Tank : 180/240 Litres
Hydraulic System : 60 Litres

Cab Features

- Fully adjustable, weight compensating operator seat with built in suspension
- Seat belt
- Cab access - side door, L/H side
- Cab light
- Windscreen wiper
- Fully enclosed and lockable
- ROP's and FOP's certified
- Roof mounted ventilation fan

Operational Weights

Front Axle : 2100
Rear Axle : 3840
Total Tare : 5940
GCM : 48000kg



Dimensions are approximate



**DESMOND
EQUIPMENT**

PORT SHEPSTONE HEAD OFFICE

Tel: 039 685 4100 | Fax: 039 685 4476 | E-mail: dezzi@venturenet.co.za
PO Box 111 Port Shepstone 4240, South Africa
Web: www.dezzi.co.za

Desmond Equipment S.A. reserves the right to modify specifications without notice.

DEALER